Pneumatic Wheels STEEL CENTRED

These steel centred pneumatic wheels are ideal for use in garden, industrial and agricultural equipment, as well as concrete mixers.

Richmond's steel centred pneumatic wheels are manufactured with one piece or three piece rims. The one piece rims are powder coated and fitted with flange ball bearings while our premium wheels are zinc plated, fitted with precision bearings and come with three piece rims offering superior strength and durability.



Nom Wheel Diameter (mm)	Tyre Width (mm)	Boss Width (mm)	Axle Diameter	Bearing Type	Tyre Size	Tyre Tread Pattern	Load Capacity (kg)	Wheel Code	
210	60	60	5/8", 3/4" or 20mm	Ball	2.50-4	Lug	100	PN8860	
215	60	60	3/4"	Flange Ball	2.50-4	Lug	100	PN8826	NEW
215	60	60	5/8", 3/4" or 20mm	Ball	2.50-4	Lug	100	PN8870	
260	83	60	5/8", 3/4" or 20mm	Ball	4.10/3.50-4	Highway	180	PN1066	
260	85	60	5/8", 3/4" or 20mm	Ball	4.10/3.50-4	Saw Tooth	180	PN1050	
260	85	54 (offset)	5/8" or 3/4"	Ball	4.10/3.50-4	Highway	180	PN1070	
260	85	54 (offset)	5/8"	Flange Ball	4.10/3.50-4	Industrial	180	PN1071	
260	80	60	3/4"	Flange Ball	4.10/3.50-4	Diamond	180	PN1080	NEW
280	60	60	3/4"	Flange Ball	2.50-6	Industrial	150	PN1100	
320	83	60	1"	Flange Ball	4.10/3.50-6	Highway	180	PN1271	
320	120	60	1"	Flange Ball	13/5.00-6	Turf	200	PN1272	
400	100	75	1"	Flange Ball	4.00-8	Knobby	200	PN1608	
400	100	75	1"	Ball	4.00x8	Knobby	200	PN1607	
400	100	75	1"	6005-1" Ball	4.00x8	Knobby	200	PN1609	NEW
400	150	75	1"	Ball	16x6.50x8	Turf	200	PN1658	
400	100	94	20mm, 1" or 25mm	Ball	4.00-8	Highway	300	PN1616 *	
400	100	100	25mm	Taper	4.00-8	Highway	300	PN1616TR *	

FOR MORE INFORMATION CONTACT OUR STAFF

1300 474 246 sales@richmondau.com www.richmondau.com

Tread Types



RICHMOND WHEEL & CASTOR CO