

Tube Type SCAFFOLD CASTORS

Richmond's range of scaffold/platform castors are compatible with Kwik Stage Steel Scaffolding and mobile Aluminium Scaffolding/Platform products.

Richmond's tube type scaffold castor is designed to accommodate a variety of scaffold tubing including Mild Steel or Aluminium with an outer diameter of 48.3mm. Solid round is also suitable with an outer diameter not exceeding 50mm. Richmond Tube Type Scaffold Castors are tested and approved to AS1576.2 2009

The adjustable scaffold castor is designed to accommodate a variety of scaffold tube including mild steel or aluminium with an outer diameter of 48.3mm and internal diameter of 39.46mm.



S883B



Diameter (mm)	Width (mm)	Wheel Type	Wheel Code	Bearing Type	Load Capacity	Swivel Code
200	50	Poly Nylon	PU8079	Roller	700	S883B

Richmond can supply many other socket and pin sizes – call 1300 474 246 or email sales@richmondau.com



S879B

Tube Type to Suit 48mm OD Tube



Diameter (mm)	Width (mm)	Wheel Type	Wheel Code	Bearing Type	Load Capacity	Swivel Code
200	50	Poly Nylon	PU8079	Roller	700	S879B

Richmond can supply many other socket and pin sizes – call 1300 474 246 or email sales@richmondau.com

Tube Type PLATFORM CASTORS

The **S551B** platform castor suits Round Solid or tubular tube with a maximum outer diameter of 38mm.



S551B



Diameter (mm)

Width (mm)

Wheel Type

Load Capacity

Swivel Code

125

35

Rebound Rubber

150

S551B

Pintle Type PLATFORM CASTORS



S6654B



Diameter (mm)

Width (mm)

Wheel Type

Wheel Code

Load Capacity

Swivel Code

150

50

Polyurethane

PU6071

400

S6654B