Stainless Elite BOLT CASTORS

Richmond's Stainless Steel Elite castors are manufactured from Grade 304 stainless steel to provide uncompromised durability when hygiene and health are important. They are highly suited to medical or laboratory equipment.

Featuring a stainless steel double ball race swivel head contributing to maintenance free life, fitted with an attractive stainless thread guard on the 100 and 125mm or plastic thread guards on the 75mm models these castors can be fitted to food carts that are constantly moved through cool rooms and steamy kitchens. They can also be hose cleaned.



SUITABLE FOR WET ENVIRONMENTS FULL STAINLESS CONSTRUCTION

Diameter (mm)	Width (mm)	Wheel Type	Wheel Code	Bearing Type	Load Capacity	Height (mm)	Swivel Radius ➤	With Brake	Bolt Hole Size (mm)	Swivel Code
75	30	Poly Nylon	PU3345	SS Ball	80/45	105	70	105	12	S3384 #
75	30	Nylon	NY3321	Plain	80/45	105	70	105	12	S3390 #
75	32	Rebound Rubber	RR3367	SS Ball	80/45	105	70	105	12	S3391 #
75	32	Elastic Rubber	ER3368	SS Ball	80/45	105	70	105	12	S3361 #
100	27	Poly Nylon	PU4439	SS Ball	100/80	133	90	106	12	S4478
100	30	Nylon	NY4417	Plain	100/80	133	90	106	12	S4490
100	32	Rebound Rubber	RR4367	SS Ball	80/45	133	90	106	12	S4491 #
100	32	Elastic Rubber	ER4368	SS Ball	80/45	133	90	106	12	S4461 #
125	27	Poly Nylon	PU5539	SS Ball	100/80	159	102	106	12	S5578
125	30	Nylon	NY5517	Plain	100/80	159	102	106	12	S5590
125	27	Poly Nylon	PU5555	Ball	100/80	159	-	106	12	S5571B
125	32	Rebound Rubber	RR5367	SS Ball	80/45	159	102	106	12	S5591 #
125	32	Elastic Rubber	ER5368	SS Ball	80/45	159	102	106	12	S5561 #

BRAKE OPTIONS: B = Brake D = Directional Lock

To order castors with Brake or Directional Lock add B or D to end of swivel code e.g. S5578B

NYLON EXPANDING PINTLES

Pintle	Pintle Code	Pintle Type				
700	IPN12-P1	For 19mm ID Round Tube				
	IPN12-P2	For 22mm ID Round Tube				
A. 3	IPN12-P3	For 28.5mm ID Round Tube				
10	INP12-P4	For 19mm ID Square Tube				
	IPN12-P5	For 22mm ID Square Tube				
A 3	IPN12-P6	For 28.5mm ID Square Tube				
	Single Bolt Fitting Various bolt lengths available					



*Also see page 96 for Solid and Threaded pintle options

CASTOR FITTING REQUIREMENTS

RICHMOND WHEEL & CASTOR CO

Fo fit this castor to a 20mm thick base requires a 50mm x 12mm stainless steel set screw. Can be fitted with a 10mm set screw using a 100RED1208SS Reducer.

FOR MORE INFORMATION CONTACT OUR STAFF

1300 474 246 sales@richmondau.com www.richmondau.com